

Ultrathin tabular grain emulsions with novel dopant managementPatent Number: ☐ EP0699950, B1Publication
date: 1996-03-06Inventor(s): DEATON JOSEPH CHARLES (US); LIGHTHOUSE JOSEPH CHARLES (US); OLM MYRA TOFFOLON (US);
WILSON ROBERT DON (US); WEN XIN (US); BLACK DONALD LEE (US); DAUBENDIEK RICHARD LEE (US);
GERSEY TIMOTHY RICHARD (US)

Applicant(s):: EASTMAN KODAK CO (US)

Requested
Patent: ☒ JP8171163Application
Number: EP19950420240 19950821Priority Number (s): US19940297430 19940826; US19940296562 19940826; US19940297195 19940826; US19940359251 19941219;
US19950441489 19950515IPC
Classification: G03C1/005 ; G03C1/08EC
Classification: G03C1/005T, G03C1/08

Equivalents: DE69517109D, DE69517109T

Abstract

A chemically and spectrally sensitized ultra-thin tabular grain emulsion is disclosed including tabular grains (a) having $\approx 111\bar{1}0$ major faces, (b) containing greater than 70 mole percent bromide, based on silver, (c) accounting for greater than 90 percent of total grain projected area, (d) exhibiting an average equivalent circular diameter of at least 0.7 μm , and (e) exhibiting an average thickness of less than 0.07 μm . It has been observed that increased speed and contrast as well as improvements in speed-granularity relationships can be realized when the surface chemical sensitization sites include epitaxially deposited silver halide protrusions forming epitaxial junctions with the tabular grains, the protrusions (a) being located on up to 50 percent of the surface area of the tabular grains, (b) having a higher overall solubility than at least that portion of the tabular grains forming epitaxial junctions with the protrusions, and (c) forming a face centered cubic crystal lattice. In further improving photographic performance by incorporating a photographically useful dopants, it has been observed that iridium placed in the ultrathin tabular grains and a shallow electron trapping site providing dopant placed, in the silver halide protrusions can together increase photographic speed and reduce high intensity reciprocity failure.

Data supplied from the esp@cenet database - 12

BEST AVAILABLE COPY